



NOTES:

1. GAUGE: 0-30 PSI WITH PROTECTIVE BOOT
2. THERMOMETER: 25-125 F°
3. RELIEF VALVE: MANUAL
4. ALUMINUM CAP, BLACK ANODIZED
5. HIGH IMPACT ACRYLIC CANISTER
6. CARBONATION TABLE FOR SUGARED PRODUCTS
7. SHIPPED WITH INSTRUCTIONS, READY TO USE

MATERIAL	NAME	DATE
	DRAWN LG	11/4/13
FINISH	ENG APPR.	
	PROPRIETARY AND CONFIDENTIAL	
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/64 ANGULAR: MACH ± 1/2° BEND ± TWO PLACE DECIMAL ± 0.015 THREE PLACE DECIMAL ± 0.005		
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASSCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASSCO MFG., INC. IS PROHIBITED.		



TITLE:
CARB TESTER ASSY, GENERIC

SIZE	DWG. NO.	REV
A	2701G_SALES	A
SCALE: 1:2	DO NOT SCALE DRAWING	SHEET 1 OF 1